

<i>Engine</i>	<i>MT-07</i>
Engine type	2-cylinder, 4-stroke, liquid-cooled, DOHC, 4-valves
Displacement	689 cm <sup>3</sup>
Bore x stroke	80.0 mm x 68.6 mm
Compression ratio	11.5 : 1
Maximum power	55.0 kW (74.8PS) @ 9,000 rpm
Maximum torque	68.0 Nm (6.9 kg-m) @ 6,500 rpm
Lubrication system	Wet sump
Clutch type	Wet, Multiple Disc
Ignition system	TCI
Starter system	Electric
Transmission system	Constant Mesh, 6-speed
Final transmission	Chain
Fuel consumption	4.3 l/100km
CO2 emission	100 g/km

<i>Chassis</i>	<i>MT-07</i>
Frame	Diamond
Front travel	130 mm
Caster angle	24° 50
Trail	90 mm
Front suspension system	Telescopic forks
Rear suspension system	Swingarm, (Link type suspension)
Rear travel	130 mm
Front brake	Hydraulic dual disc, Ø 282 mm
Rear brake	Hydraulic single disc, Ø 245 mm
Front tyre	120/70 ZR 17M/C(58W) (Tubeless)
Rear tyre	180/55 ZR 17M/C(73W) (Tubeless)

<i>Dimensions</i>	<i>MT-07</i>
Overall length	2,085 mm
Overall width	745 mm
Overall height	1,090 mm
Seat height	805 mm
Wheel base	1,400 mm
Minimum ground clearance	140 mm
Wet weight (including full oil and fuel tank)	182 kg
Fuel tank capacity	14 L
Oil tank capacity	3.0 L